

CLEAN IT – BEFORE – YOU STICK IT

- Use a warm, damp cloth or sponge to clean the wall, door surface and skirting boards and allow it to completely dry, we suggest you do this 24 hours before installation. Make sure all previous cleaning solutions are completely gone. Give the floor a sweep also so the prints don't collect any dust particles.
- If the wall/door is recently painted wait until the wall is completely dry and cured before installing the decal. We recommended waiting 30 days before installing decal on newly painted surfaces.
- The surface should also be free of imperfections such as cracks, holes, surface damage, chipped/flaking paint and moisture, where possible remove any picture hooks or light/power switch casings.
- Imperfections may seem amplified once the decal has been applied, so taking the time to repair and prepare the wall correctly will guarantee the best result. Using a primer such as “Viponds – Self Adhesive Prep Coat” to the wall prior to installation is suggested in order to achieve the best result possible and assist in longevity, however it is not essential.

PEEL & STICK IT

- You will need clean hands, a ladder, pencil, a sharp utility knife, a straight edge ruler/plastic scraper, tape measure & spirit level.
- Before you commence, measure the wall & use the spirit level to ensure the top or side edge to view how level each edge is. Most edges are not level, you may need to mark a line to follow with the decal edge.
- Depending on the size of your decal it may be helpful to have two people install it. Try not to let the adhesive come together, or let the wallpaper fold up against itself. It's okay if it does, you can separate it by carefully pulling it apart and you may want two people to do this on larger images.
- Lay the decal face down on a table or clean surface.
- Start at the top of your decal and pull down approximately 30cm of the backing paper and crease the back of the backing paper. Lift the decal from the top corners & approach surface & apply corners of the decal. Simply apply the 30cm of exposed adhesive area to your chosen location. It can be repositioned many times.
- Once you're square then continue to slowly pull the backing paper downward in 30cm increments, smoothing the wallpaper as you go. Depending on the size, it may be helpful if one person pulls down the backing paper, while the

other smooths the surface over the wall especially the edges. Don't rub too hard or you may damage the print.

- You can use a felt squeegee to smooth out any bubbles and wrinkles or lightly press and smooth them out working outwards pushing any bubbles to the edge of the paper. Alternatively; you can just peel back that area and re-apply by working from the centre of the graphic going outwards.
- Applying the first panel is tricky so take your time to get it right at the top and edges. Don't worry about the excess it can be trimmed off later with a sharp knife.
- Once all the panels are installed, trim off any excess decal using a sharp blade along the top, bottom and power points.
- After installation is complete wipe the entire decal with a soft dry cloth to remove any dust or residue from the application process.

SUGGESTIONS

- If a bubble re-appears over the next day or two, pressing and lightly rubbing can remove it. This can happen occasionally if oil, dirt, or dust is on your surface. Use a sewing pin to pop the bubble, and then smooth it out with your fingers in a circular motion.
- In the very rare instance that bubbles keep re-appearing, you may want to move your decal to another area as there is something preventing the adhesive to stick. Most causes of bubbles are because the wall was painted within the last 30 days or cleaning chemicals were used prior.

DISCLAIMER

- There are so many different types of wall paints and other variables affecting the application success of this product, it is imperative that the end user determine the suitability of this product for the application. Bailey Print Group **will not** be held liable for any cost resulting from a failed application of this decal. The user assumes all risk and cost associated with the application of this product. In the event of a failure and Bailey Print Group, at its sole discretion determines the material had manufacturing defects contributing to the failure, will replace the decal.

WARRANTY

- Our product & prints are covered by a two-year warranty. The warranty covers the print stock & inks for the duration of two years when internally applied as per the written instructions in this document.